

EXMARK

Navigator ZT Rider

Specs:

Model: **NAV20KC** 20HP Kohler Zero Turn

Cutting Width: 42" or 48"

Cutting Height: 1" to 4"

Drive System: Dual Hydro-Gear 12cc variable displacement

Speed: 0-7 mph forward, 0-5.5 mph reverse

Fuel Capacity: 7.5 gallon w/ pivoting tank

Bag or Mulching available.

Larger 5" x 11" diameter blower generates enhanced airflow for optimum vacuuming.



Lazer Z Advantage Series ZT Rider

Specs:

Model: **LZAS25KC604** 25HP Kohler Command, **LZAS29KA724** 29HP Kawasaki V-Twin

Cutting Width: 60" & 72"

Cutting Height: 1"-5.5" in .25" increments adjustable from the operator's seat

Drive System: 12cc pumps and 14.5 cubic inch motors with integrated shock valve

Speed: 0-10 mph forward, 0-6 mph reverse

Fuel Capacity: 12 gallon single fuel tank with single fill location

Full floating UltraCut® Series 4.

Side discharge standard with the option to bag or mulch.



Lazer Z ZT Rider

Specs:

Model: **LZZ27KC606** 27HP Kohler Command, **LZZ34KA726** 34HP Kawasaki V-Twin

Cutting Width: 60" & 72"

Cutting Height: 1" – 5.5" in .25" increments adjustable from the operator's seat

Drive System: 16cc pumps and 17.1 cui motors

Speed: 0-11.5 mph forward, 0-7 mph reverse

Fuel Capacity: 12 gallon single fuel tank with single fill location

Full floating UltraCut® Series 6 featuring the heavy-duty Triton® spindle.

Side discharge standard with the option to bag or mulch.



Lazer Z® XS ZT Rider

Specs:

Model: **LXS25KD605** 25HP Kubota® 3-Cylinder Liquid-Cooled Diesel

Cutting Width: 60"

Cutting Height: 1" – 5." in .25" increments adjustable from the operator's seat

Drive System: Two Hydro-Gear 21cc/rev pumps with integral SCR valves

Speed: 0-12 mph forward, 0-8 mph reverse

Fuel Capacity: 15.5 twin fuel tanks

Triton® High-Capacity Cutting Deck side-discharge standard with option to bag or mulch.



Metro® 21 Mower

Specs:

Model: **MSHN21** 5.5HP Honda, **MSHN21B** 5.5HP Honda (BBC)

Cutting Width: 21"

Cutting Height: .75" to 3.25" in .5" increments.

Engine Deck: Die-cast aluminum.

Safety Package: Zone Start or Blade Brake Clutch (BBC)

Drive System: Self-propelled rear-wheel gear-drive.

Transmission: 3-Speed

Speed Control: Finger-tip control.

Speed 2.0 mph to 4.1 mph

Fuel Capacity: 2.1 quarts

Rear-discharge bagger standard with option to side-discharge or mulch.



Metro® 26 Mower

Specs:

Model: **MS6KA26B** 6HP Kawasaki

Cutting Width: 26"

Cutting Height: 1" to 4" in .5" increments.

Engine Deck: Die-cast aluminum.

Safety Package: Blade Brake Clutch (BBC)

Drive System: Self-propelled rear-wheel gear-drive.

Transmission: 3-Speed

Speed Control: Finger-tip bail controls.

Speed 2.0 mph to 4.1 mph

Fuel Capacity: 1 gallon

Rear-discharge bagger standard with option to side-discharge or mulch.

