

HONDA

Generators - Super Quiet

Specs:

Model: **EU1000IAN** 50cc with GXH50 Engine, **EU3000ISAN** 196cc with GX200 Engine, **EU6500ISA** 389cc with GX390 Engine

AC Output: 120V 1000W, 120V 3000W, 120/240V 6500W

Starting System: Recoil; Recoil & Electric; Recoil & Electric

Fuel Tank Capacity: .6 gal., 3.4 gal., 4.5 gal.

Run Time per Tankful: 3.8 hrs @ rated load, 8.3 hrs. @ ¼ load; 7.2 hrs. @ rated load, 20 hrs @ ¼ load; 4.7 hrs @ rated load, 14 hrs. @ ¼ load

Dimensions (LxWxH): 17.7" x 9.4" x 15.0"; 25.8" x 18.9" x 22.4"; 33.5" x 26.4" x 27.5"

Noise Level: 59 dB @ rated load; 58 dB @ rated load; 60 dB rated load

Dry Weight: 29 lbs., 134 lbs., 253 lbs.



Specs:

Model: **EU2000** 98.5cc with GX100 Engine

AC Output: 120V 2000W

Starting System: Recoil

Fuel Tank Capacity: .95 gal.

Run Time per Tankful: 4 hrs @ rated load, 15 hrs. @ ¼ load

Dimensions (LxWxH): 20.1" x 11.4" x 16.7"

Noise Level: 59 dB @ rated load

Dry Weight: 46.3 lbs.

- **EU2000IA Companion** has built in 30A outlet for easy parallel capability with another EU2000i.

- **EU2000IA Camo** has Natural Gear™ camo exterior.



Generators - Industrial

Specs:

Model: **EB3000** 196cc with GX200 Engine, **EB5000** 337cc with GX340 Engine

AC Output: 120V 3000W, 120/240V 5000W

Starting System: Recoil

Fuel Tank Capacity: 2.7 gal., 6.6 gal.

Run Time per Tankful: 6 hrs @ rated load, 9.39 hrs. @ ½ load; 8.3 hrs. @ rated load, 11.9 hrs

Dimensions (LxWxH): 17.3" x 15.7" x 18.9"; 41.9" x 27.2" x 29.2"

Noise Level: 68 dB @ rated load; 72 dB @ rated load

Dry Weight: 68.4 lbs., 214 lbs.



Specs:

Model: **ES6500** 359cc with GX360 Engine

AC Output: 120/240V 6500W

Starting System: Electric

Fuel Tank Capacity: 4.4 gal.

Run Time per Tankful: 4.6 hrs @ rated load, 6.9 hrs. @ ½ load

Dimensions (LxWxH): 46.9" x 28.0" x 26.8"; 41.9" x 27.2" x 29.2"

Noise Level: 74.5 dB @ rated load

Dry Weight: 284 lbs.



Generators - Economy

Specs:

Model: **EG3500** 242cc with GX240 Engine, **EG5000** 337cc with GX340 Engine

AC Output: 120/240V 3500W, 120/240V 5000W

Starting System: Recoil

Fuel Tank Capacity: 1.6 gal., 1.9 gal.

Run Time per Tankful: 3.2 hrs @ rated load, 5.1 hrs. @ ½ load; 2.4 hrs. @ rated load, 3.6 hrs

Dimensions (LxWxH): 25.8" x 18.1" x 18.1"; 25.8" x 18.9" x 19.1"

Noise Level: 72 dB @ rated load; 76 dB @ rated load

Dry Weight: 118 lbs., 147 lbs.



Specs:

Model: **EN2500** 160cc with GC160 Engine, **EP2500** 160cc with GX160 Engine

AC Output: 120V 2500W, 120V 2500W

Starting System: Recoil

Fuel Tank Capacity: 2.9 gal., 3.83 gal.

Run Time per Tankful: 7.3 hrs @ rated load, 11 hrs. @ ½ load; 10.2 hrs. @ rated load, 15.3 hrs

Dimensions (LxWxH): 21.3" x 17.5" x 17.3"; 23.5" x 17.1" x 17.2"

Noise Level: 76 dB @ rated load; 69 dB @ rated load

Dry Weight: 71 lbs., 99 lbs.



Generators - Deluxe

Specs:

Model: **EM5000** 337cc with GX340 Engine, **EM6500** 389cc with GX390 Engine

AC Output: 120/240V 5000W, 120/240V 6500W

Starting System: Recoil or Electric

Fuel Tank Capacity: 6.6 gal.

Run Time per Tankful: 8.3 hrs @ rated load, 11.9 hrs. @ ½ load; 5.3 hrs. @ rated load, 10 hrs

Dimensions (LxWxH): 41.9" x 27.2" x 29.2"; 41.9" x 27.2" x 29.2"

Noise Level: 72 dB @ rated load; 75 dB @ rated load

Dry Weight: 223 lbs., 227 lbs.



Generators - Deluxe

Specs:

Model: **EM5000** 337cc with GX340 Engine, **EM6500** 389cc with GX390 Engine

AC Output: 120/240V 5000W, 120/240V 6500W

Starting System: Recoil or Electric

Fuel Tank Capacity: 6.6 gal.

Run Time per Tankful: 8.3 hrs @ rated load, 11.9 hrs. @ ½ load; 5.3 hrs. @ rated load, 10 hrs

Dimensions (LxWxH): 41.9" x 27.2" x 29.2"; 41.9" x 27.2" x 29.2"

Noise Level: 72 dB @ rated load; 75 dB @ rated load

Dry Weight: 223 lbs., 227 lbs.



Tillers - Mini

Specs:

Model: **FG110AT** 25cc with GX25 Engine
Tilling Width: 9"
Tine Diameter: 8"
Fuel Capacity: .60 qt.
Transmission Speed: 1 - forward
Tine Speed: 294 rpm
Transmission Type: Worm Gear
Dry Weight: 24.9 lbs.



Tillers - Mid-Tine

Specs:

Model: **F220** 57cc with GXV57 Engine, **FC600** 163cc with GX160 Engine
Tilling Width: 21", 26.4"
Tine Diameter: 11", 13"
Fuel Capacity: .72 qt., 2.8 qt.
Transmission Speed: 1 - forward
Tine Speed: 130 rpm, 78 rpm
Transmission Type: Gear Drive, Chain Drive
Dry Weight: 49.6 lbs., 130 lbs.



Tillers - Rear-Tine

Specs:

Model: **FRC800** 242cc with GX240 Engine
Tilling Width: 20"
Tine Diameter: 12"
Fuel Capacity: 4.8 qt..
Transmission Speed: 3 - forward, 1 - reverse
Tine Speed: 219 rpm
Transmission Type: Chain Drive
Dry Weight: 275 lbs.



Pumps - General Purpose

Specs:

Model: **WB20** 118cc with GX120 Engine, **WB30** 163cc with GX160 Engine
Pump type: Centrifugal, Self-priming
Discharge Capacity: 152 gal./min.; 275 gal./min.
Suction Port Diameter: 2" NPT; 3" NPT
Discharge Port Diameter: 2" NPT; 3" NPT
Total Head Lift: 92 ft.; 85 ft.
Max. Pressure: 40 psi; 37 psi
Dimensions (LxWxH): 17.9" x 14.4" x 16.5"; 20.1" x 15.2" x 17.9"
Dry Weight: 46 lbs.; 60 lbs.



Pumps - Multi Purpose

Specs:

Model: **WMP20** 163cc with GX160 Engine
Pump type: Multi-purpose Centrifugal, Self-priming
Discharge Capacity: 220 gal./min.
Suction Port Diameter: 2" NPT
Discharge Port Diameter: 2" NPT
Total Head Lift: 105 ft.
Max. Pressure: 45 psi
Dimensions (LxWxH): 20.5" x 15.7" x 17.7"
Dry Weight: 56 lbs.



Pumps - Construction - Trash

Specs:

Model: **WT30** 242cc with GX240 Engine
Pump type: Trash Centrifugal Self-priming
Discharge Capacity: 319 gal./min.
Suction Port Diameter: 3" NPT
Discharge Port Diameter: 3" NPT
Total Head Lift: 89 ft.
Max. Pressure: 39 psi
Dimensions (LxWxH): 26.0" x 19.5" x 10.3"
Dry Weight: 132 lbs.



Pumps - De-Watering

Specs:

Model: **WX10** 25cc with GX25 Engine
Pump type: General purpose Centrifugal Self-priming
Discharge Capacity: 37 gal./min.
Suction Port Diameter: 1" NPT
Discharge Port Diameter: 1" NPT
Total Head Lift: 118 ft.
Max. Pressure: 51 psi
Dimensions (LxWxH): 12.8" x 8.7" x 11.8"
Dry Weight: 13.4 lbs.



Trimmers

Specs:

Model: **HHT25SLTA** 4 Cycle 25cc with GX25, **HHT35SUKAT** 4 Cycle 35.8cc with GX35
Fuel Tank Capacity: 16.9fl.oz, 22 fl.oz.
Dry Weight: 13lbs, 15.4lbs
Drive Shaft: Flexible Steel Cable
Cutting Width: 17"



Snowblowers - Single Stage

Specs:

Model: **HS520** 160cc with GX160,

Starting System: Recoil

Fuel Capacity: .3 gal.

Operational Cap. per tankful: 1.6 hours

Drive Mechanism: Manual, Auger-assisted

Stages: Single

Chute Turning Radius: 220°

Clearing Width: 20"

Clearing Height: 12"

Discharge Distance: 26'

Dry Weight: 76 lbs

Also available in Electric Start.



Snowblowers - Two Stage

Specs:

Model: **HS928** 270cc with GX270,

Starting System: Recoil/Electric

Fuel Capacity: 1.58 gal.

Operational Cap. per tankful: 2.5 hours

Drive Mechanism: Hydrostatic Infinitely Variable

Stages: 2

Chute Turning Radius: 210°

Clearing Width: 28"

Clearing Height: 20.1"

Discharge Distance: 49'

Dry Weight: 218 lbs



Lawnmowers - HRR Series

Specs:

Model: **HRR2165PDA**, **HRR2165VKA**, **HRR2165VXA** all with GCV160 Engine

Deck Material: Steel

Cutting Width: 21"

Mowing Height: 3/4" - 3.25", 3/4" - 3.25", 3/4" - 4"

Mowing Height Adjustments: 6, 6, 7

Transmission: None, Multi position SmartDrive, Multi position SmartDrive

Ground Speed: N/A, 0 to 3.6 mph, 0 to 3.8 mph

Starter: Recoil

Choke System: Manual, Automatic, Manual

Drive: None, Belt, Belt

Bag: Standard

Bag Capacity: 2.4 bushels

Blade: Twin Blades (QuadraCut)

Blade Control: Flywheel brake, Flywheel brake, BBC (Roto-Stop)

Dry Weight: 78 lbs., 83 lbs., 97 lbs.



Lawnmowers - HRX Series

Specs:

Model: **HRX2172VKA, HRX2172HXA, HRX2172HMA** all with GCV190 Engine

Deck Material: Nexite™

Cutting Width: 21"

Mowing Height: ¾" - 4"

Mowing Height Adjustments: 7

Transmission: Multi position SmartDrive, Cruise Control (Hydrostatic), Cruise Control (Hydrostatic)

Ground Speed: 0 to 3.6 mph, 0 to 4 mph, 0 to 4 mph

Starter: Recoil, Recoil, Electric/Recoil

Choke System: Automatic, Manual, Manual

Drive: Belt, Belt, Belt

Bag: Standard

Bag Capacity: 2.5 bushels

Blade: Twin Blades (MicroCut)

Blade Control: Flywheel brake, BBC (Roto-Stop), BBC (Roto-Stop)

Dry Weight: 89 lbs., 96 lbs., 98 lbs.



Lawnmowers - Commercial Series

Specs:

Model: **HRC2163PDA** with GXV160 Engine, **HRC2163HXA**, with GXV160 Engine

Deck Material: Heavy Duty 15 ga Steel

Cutting Width: 21"

Mowing Height: ¾" - 4"

Mowing Height Adjustments: 8

Transmission: None, Cruise Control (Hydrostatic)

Ground Speed: N/A, 1.8 to 4 mph

Starter: Recoil

Choke System: Manual

Drive: None, Shaft

Bag: Standard

Bag Capacity: 2.5 bushels

Blade: Twin Blades (MicroCut)

Blade Control: Flywheel brake, BBC (Roto-Stop)

Dry Weight: 97 lbs., 122 lbs.

