

TORO

Homeowner - Recycler®

Specs:

Model: **20064, 20065, 20066, 20067, 20068**

Engine: 20064, 20065 6.5HP B&S; 20066, 20067, 20068 6.75HP B&S with Ready Start

Starter: Recoil, Recoil, Recoil, Electric, Electric

Drive System: 20064, 20065 Variable Speed; 20066, 20067, 20068 Personal Pace

Blade Override System: N/A on all Models except 20068

Mulch/Rear Bag/Side Discharge: Standard on all Models

Cutting Width: 22"

Deck Material: Steel

Cutting Height: 1.25" - 4.25"

Wheel Height: 8" in on all Models except 20065 - 8" Front, 11" Rear

Weight: 80 lbs, 83 lbs, 83 lbs, 90 lbs, 91 lbs



Homeowner - Super Recycler®

Specs:

Model: **20090, 20092, 20093, 20095**

Engine: 6.75HP B&S

Starter: Recoil, Recoil, Recoil, Key-Lectric®

Drive System: 20090 Push; 20092, 20093, 20095 Personal Pace Rear Wheel Drive

Blade Override System: N/A on all Models except 20093

Mulch/Rear Bag/Side Discharge: Standard on all Models Except 20090 Bag Optional

Cutting Width: 21"

Deck Material: Cast-Aluminum

Cutting Height: 1.25" - 4.25"; 7 Position

Weight: 69 lbs, 83 lbs, 95 lbs, 95 lbs



Homeowner - Recycler®

Specs:

Model: **20331, 20332, 20333**

Engine: 20331 6.5HP B&S; 20332 & 20333 6.75HP B&S

Starter: Recoil

Drive System: 20331 Variable Speed; 20332 & 20333 Personal Pace

Blade Override System: N/A on all Models except 20333

Mulch/Rear Bag/Side Discharge: Standard on all Models

Wheel Height: 8" Front, 11" Rear on 20331 Only

Cutting Width: 22"

Deck Material: Steel

Cutting Height: 1" - 4"

Weight: 81 lbs, 80 lbs, 88 lbs



Commercial Walk Behind Mowers

Specs:

Model: **22195, 22196**

Engine: 5.5HP GXV160 Honda

Starter: Recoil

Ground Speed: Self Propelled 2.0 - 4.2 mph

Transmission: 3-Speed Rear Wheel Drive

Deck: ¼" die cast aluminum - Recycler® & Rear Bagger

Crankshaft: 25mm with steel protector

Lubrication: Forced lubrication

Height of Cut: ¾" - 3 ¼" in ½" increments

Wheels: Steel with ball bearings

Fuel Capacity: .53 gal

Bagger Capacity: 2.5 bushels

22196 Model has Blade Brake Clutch (BBC) - Allows engine to run with blade stopped.



Commercial Walk Behind Mowers

Specs:

Model: **22164**

Engine: 6.0HP FJ180V Kawasaki

Starter: Recoil

Ground Speed: Variable up to 4 mph

Transmission: 3-Speed Rear Wheel Drive

Deck: corrosion-resistant aluminum

Crankshaft: 25mm

Lubrication: Forced lubrication

Height of Cut: 1 ¼" - 4 ¼"

Wheels: Steel with ball bearings

Fuel Capacity: .53 gal



Lawn Tractors - LX Series

Specs:

Model: **LX426, LX425, LX466, LX468**

Engine: 20HP B&S, 20HP Kohler, 22HP B&S, 22HP Kohler

Transaxle Type: LX426 & LX 425 - Automatic CVT; LX 466 & LX 468 - Hydrostatic

Ground Speed: 0 - 5.5 mph, 0 - 2.3 mph reverse

Ignition: Electronic Keystart

PTO Clutch: Manual on all Models Except Electric on LX468

Deck: LX426 & LX425 - 42" 2-blades; LX466 & LX468 - 46" 3-blades

Fuel Capacity: 3 gal

Turning Radius: 18"

Cutting Height: 1.5" - 4"

Dimensions (L x W x H): 71" x 38" x 42"

Weight: LX426 & LX425 - 575 lbs; LX466 & LX468 - 630 lbs

Attachments: Mulch Kit, Twin Bagger, Snowthrower, & Dozer Blade



Snow Blowers - Electric

Specs:

Model: **38361, 38025**

Capacity/Minute: Up to 300 lbs, Up to 700 lbs

Throw Distance: Up to 20', Up to 30'

Clearing Width: 12", 18"

Snow Cut Depth - 1 Pass: 6", 10"

Rotor Style: Single Piece, 2-Blade, Curve Rotor

Weight: 13 lbs, 24 lbs



Snow Blowers - Single Stage

Specs:

Model: **38172/38182, 38515, 38581/38582**

Engine: Tecumseh® 2-Cycle on 38172/38182; Toro R*tek® 2-Cycle on all other Models

Displacement: 98cc, 141cc, 141cc

Starter: Recoil/Electric, Recoil, Recoil/Electric

Fuel Capacity: .9 qt, 1.0 qt, 1.1 qt

Capacity/Minute: Up to 1100 lbs, Up to 1700 lbs, Up to 1700 lbs

Throw Distance: Up to 25', Up to 30', Up to 30'

Clearing Width: 16", 20", 21"

Snow Cut Depth - 1 Pass: 11", 13", 12.5"

Auger or Rotor Style: Rubber Paddles

Weight: 37/39 lbs, 71 lbs, 72/74 lbs



Snow Blowers - Two-Stage

Specs:

Model: **38640**

Engine: 10HP Tecumseh® Snow King 4-Cycle

Starter: Electric

Fuel Capacity: 1 gal

Capacity/Minute: Up to 2100 lbs

Throw Distance: Up to 45'

Clearing Width: 28"

Snow Cut Depth - 1 Pass: 21"

Weight: 249 lbs



Timecutter® Z Zero-Turn Riders

Specs:

Model: **74360, 74363, 74373, 74375**

Engine: 19HP, 21HP, 23HP, 25HP Kohler Engine

Fuel Capacity: 3 gal

Mowing Deck: 42", 42", 50", 50"

Transmission: Hydro Gear/EZT

Tires (Rear): 18" x 7.5", 18" x 7.5", 18" x 9.5", 18" x 9.5"

Tires (Front): 10" x 4", 10" x 4", 11" x 4" Smooth, 11" x 4" Smooth

Seat: 15" High Back, 18" Extra Tall for 74363, 74373, 74375

Armrests: Optional on all Models except Standard on Model 74375



Titan Zero Turn Riders

Specs:

Model: **74818, 74823**

Engine: 23HP & 25HP Kohler® Engine

Fuel Capacity: 5 gal

Ground Speed (f/r): 7.5/3.8 mph

Mowing Deck: 54", 60"

Cutting Height: 1.5" - 4.5" ¼" increments

Transmission: Hydro Gear ZT2800 with Charge Pumps

Tires (Rear): 20" x 10"

Tires (Front): 11" x 4" Smooth

Seat: 18" Extra Tall with slide and adjustable seat spring suspension.

Armrests: Standard



Commercial Zero-Turn Riders

Specs:

Model: **74449, 74292**

Engine: 21HP Kawasaki®, 27HP Kohler®

Fuel Capacity: 10 gal, 12 gal

Ground Speed (f/r): 8.5/4.9, 8.5/5

Mowing Deck: 52", 60"

Cutting Height: 1.5" - 4.5" ¼" increments, 1.5" - 5" ¼" increments

Hydraulic Pumps: Hydro-Gear 10cc

Drive Tires: 23" x 9.5" - 12", 24" x 12" - 12"



TORO DINGO

Compact Utility Equipment: Tracked Model

Specs:

Model: **22306 TX 420** 20HP Kohler® Command PRO™

Cooling System: Air Cooled

Hydraulic System Pressure: 3000 psi system relief pressure

Flow: 11.2 mpg

Reservoir Capacity: 10.5 gallons

Track: Standard, Endless Kevlar rubber

Controls: Key, Throttle, Choke

Steering: Single control w/ ref. bar

Loader/Hydraulic System: Joystick control for all functions

Dimensions: Grid Clearance: 4.6"

Overall Length: 92"

Overall Width: 33.7"

Overall Height: 46.1"

Hinge Pin Height: 65.8"

Ground Speed: 0-4.5 mph fwd, 1-2 rev.

Tip Capacity: 1480 lbs.

Rated Operating Capacity: 500 lbs.

Weight (w/o narrow bucket): 1830 lbs.



Compact Utility Equipment: Tracked Model

Specs:

Model: **22308 TX 413** 13HP Honda® GX390, 4-cycle
Cooling System: Air Cooled
Hydraulic System Pressure: 2650 psi system relief pressure
Flow: 7 mpg
Reservoir Capacity: 10.5 gallons
Track: Standard, Endless Kevlar rubber
Controls: Key, Throttle, Choke
Steering: Single control w/ ref. bar
Loader/Hydraulic System: Joystick control for all functions
Dimensions: Grid Clearance: 6.1”
Overall Length: 86.7”
Overall Width: 33.7”
Overall Height: 42.5”
Hinge Pin Height: 48”
Ground Speed: 0-3 mph fwd, 0-1.5 rev.
Tip Capacity: 1200 lbs.
Rated Operating Capacity: 420 lbs.
Weight (w/o narrow bucket): 1340 lbs.



Compact Utility Equipment: Wheeled Model

Specs:

Model: **22317 220** 20HP Kohler® Command Pro™
Cooling System: Air Cooled
Hydraulic System Pressure: 2650 psi system relief pressure
Air Filter: Standard Dry Type Air Cleaner
Hydraulic System Pressure: 3000 psi
Low Flow Pump: 4mpg
High Flow Pump: 10.8mpg
Hydraulic Reservoir Cap.: 14.8 gallon
Wheels and Tires: Std Tires: 18x8.5-8, 8ply
Controls: Key, Throttle, Choke
Steering: Zero turning type w/ 2 levers
Loader/Hydraulic System: 2 control levers-push/pull
Ground Clearance: 5.0” front & rear
Overall Length: 62”, 82.8” w/ bucket
Overall Width: 40.5” std tires, 35” narrow
Overall Height: 48.7”, 91.2” std bucket at highest
Hinge Pin Height: 66”
Tip Capacity (max lift): 1,030 lbs w/ 200lb operator
SAE Rated Oper. Cap.: 515 lbs w/ 200lb operator
Weight w/o Bucket: 1576 lbs



Compact Utility Equipment: Diesel Tracked Model

Specs:

Model: **22319 TX 525** 25HP Kubota® Diesel engine
Cooling System: Liquid Cooled
Hydraulic System Pressure: 3000 psi relief
Auxiliary Flow: 13.8 mpg
Loader Arm Flow: 6 mpg
Traction Flow: 16.9 mpg
Reservoir Capacity: 10.5 gallons
Track: Endless Kevlar reinforced rubber
Controls: Key, Throttle, Choke
Steering: Single control w/ ref. bar
Loader/Hydraulic system: Joystick control for all functions
Dimensions: Grade Clearance 4.6”
Overall Length: 70.7”
Overall Width: 33.7”
Overall Height: 46.1”
Hinge Pin Height: 65.8”
Ground Speed 0-4.5 mph fwd, 0-2 mph rev.
Tip Capacity: 1580 lbs.
Rated Operating Capacity at 35% tip: 553 lbs.
Weight: 1904 lbs.
Ground Pressure: 5.2 psi



Compact Utility Equipment: Walk Behind Trencher

Specs:

Model: **22970 TRX** 15HP Kawasaki® Twin-Cylinder Engine
Cooling System: Air cooled
Hydraulic system: Pressure 2900 psi
Flow: 10mpg auxiliary, 9.2mpg each traction circuit
Fuel Tank Capacity: 2.1 gallons
Engine Oil Capacity: 1.9 quarts
Hydraulic Oil Capacity: 6.3 gallons
Track: 5.9” wide – endless nylon reinforced rubber track
Steering: Single control w/ ref. bar
Overall Length (boom up): 82.5”
Overall Width: 33.8”
Overall Height: 46” at controls
Wheel Base: 23”
Weight: 1100 lbs.
Headshaft Speed: 226 RPM w/ 315 ft/lbs of torque
Transport Speed: 3.1 mph fwd, 1.5 mph rev.
Boom Options: 24” and 36” depth, 4” and 6” width
Chain Types: 2-pitch chain w/ 4-pitch soil-cup tooth,
2-pitch combo chains (rock & soil)
2 pitch Shark® welded rock tooth



Compact Utility Equipment: Walk Behind Trencher

Specs:

Model: **22971 TRX** 19 hp Kawasaki® Twin-Cylinder Engine

Cooling System: Air cooled

Hydraulic system: Pressure 2900 psi

Flow: 10mpg auxiliary, 9.2mpg each traction circuit

Fuel Tank Capacity: 2.1 gallons

Engine Oil Capacity: 1.9 quarts

Hydraulic Oil Capacity: 6.3 gallons

Track: 5.9" wide – endless nylon reinforced rubber track

Steering: Single control w/ ref. bar

Overall Length (boom up): 82.5"

Overall Width: 33.8"

Overall Height: 46" at controls

Wheel Base: 23"

Weight: 1185 lbs.

Headshaft Speed: 226 RPM w/ 385 ft/lbs of torque

Transport Speed: 3.1 mph fwd, 1.5 mph rev.

Boom Options: 24" and 36" depth, 4" and 6" width

Chain Types: 2-pitch chain w/ 4-pitch soil-cup tooth,

2-pitch combo chains (rock & soil)

2 pitch Shark® welded rock tooth



Compact Utility Equipment: Attachments

22409 - Standard Bucket



22445 - Tiller



22802-High Torque Auger Power Head



22414 - Utility Blade



22465 - 2' High Speed



22804-TX 413 Auger Power Head



22422 - Compact Bucket



22471 - 3' High Speed



22999 - TX 413 Trailer



22438 - Hydraulic Tree Forks



